MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER:	: 452				
IDENTITY: WIPE OUT	T (FC)	20A	Revision Date:	01/18/2007	
Section I					
Manufacturer's Name	e: THREE	G INDUS	TRIAL SUPPLY *	Telephone Numbe	ers:
Address:	P. O. B	30X 3712		Emergency: 800/255-3924	
	VICTO	DRIA		Information:	
	State:	TX Zip Co	ode: 77903	361/578-3200	
HMIS CODES: RE	ΞΑϹΤΙVΙΤΥ	Y: 1	FLAMMABILITY: 3	HEALTH: 2	PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
AROMATIC PET. DISTILLATES ISOPROPYL ALCOHOL NAPTHALENE *+ PROPANE/N-BUTANE	64742-94-5 67-63-0 91203 68476-86-8	NOT EST. 400 PPM 10 PPM 1000 PPM	NOT EST. 200 PPM 10 PPM 600 PPM	N/A N/A N/A N/A	

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	350F+	Specific Gravity (water=1)	0.89
Vapor Pressure(mm Hg)	<5	Melting Point:	N/A
Vapor Density(AIR=1)	4	Evaporation Rate:	<1
Solubility in Water:	0%	(Butyl Acetate=1)	
Appearance and Odor:	BROWN COLC	ORED SPRAY, PETROLEUM ODOR	

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): 142F TCC Flammable Limits: LEL: 1.0 UEL: 6.0 Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS

Section V: REACTIVITY DATA	PRODUCT NUMBER: 452			
	ons to avoid: RATURES ABOVE 120 F, HOT SURFACES			
Incompatibility (Materials to Avoid):	SOME PLASTICS			
Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY PRODUCE CARBON MONOXIDE.				
Hazardous Polymerization: Conditions to Avoid: NONE KNOW	May Occur: Will Not Occur: X			
Section VI: HEALTH HAZARD DATA				

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards (Acute and Chronic):

- INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY LEAD TO UNCONSCIOUSNESS.
- INGESTION: NAUSEA.
- SKIN: IRRITATION AND REDDENING.
- EYES: IRRITATION AND REDDENING.

Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NO

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL AGGRAVATE RESPIRATORY CONDITIONS.

Emergency and First Aid Procedures:

- INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF INDICATED.
- EYES: FLUSH WITH WATER FOR 15 MINUTES AND CALL PHYSICIAN.
- SKIN: WASH WITH SOAP AND WATER.
- INGESTION: DO **NOT** INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in Case Material is Released or Spilled:

• WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method:

• DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Precautions to be taken in handling and storing:

- DO NOT PUNCTURE OR INCINERATE CONTAINER.
- DO NOT REUSE EMPTY CONTAINER.
- WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Other Precautions:

- DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.
- EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.
- VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREAS. Ventilation: Local Exhaust: ADEQUATE Mechanical: N/A Special: N/A Other: N/A Protective Gloves: RECOMMENDED Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED. Other Protective Clothing or Equipment: N/A Work/Hygienic Practices: WASH HANDS AFTER USE