

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 569

IDENTITY: RELEASE 20A Revision Date: 01/19/2007

Section I

Manufacturer's Name: THREE G INDUSTRIAL SUPPLY * Telephone Numbers:

Address:	P. O. BOX 3712	Emergency:
	VICTORIA	800/255-3924
	State: TX Zip Code: 77903	Information:
		361/578-3200

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 2 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
HYDROTREATED NAPTH. DIST	64742-52-5	5 MG/M3	5 MG/M3	N/A	_____
MINERAL SPIRITS	8052-41-3	500 PPM	100 PPM		_____
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	600+	F Specific Gravity (water=1)	0.92
Vapor Pressure(mm Hg)	<.01	Melting Point:	N/A
Vapor Density(AIR=1)	N/A	Evaporation Rate:	<.1
Solubility in Water:	0%	(Butyl Acetate=1)	
Appearance and Odor:	STRAW COLORED LIQUID, MILD PETROLEUM ODOR		

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): +200F TCC

Flammable Limits: LEL: N/A UEL: N/A

Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER

Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. **FLAMMABLE.**

EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 569

Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120 F

Incompatibility (Materials to Avoid): NONE

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: N/A

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards (Acute and Chronic):

- INHALATION: DIZZINESS.
- INGESTION: NAUSEA, SICKNESS.
- EYES: IRRITATION.
- SKIN: MAY CAUSE LOCALIZED DRYNESS.

Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NO

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures:

- INHALATION: REMOVE TO FRESH AIR. CONSULT PHYSICIAN IF DIFFICULTY IN BREATHING PERSISTS.
- EYES: FLUSH THOROUGHLY WITH WATER FOR 15 MINUTES.
- SKIN: FLUSH WITH WATER. CONSULT PHYSICIAN IF NEEDED.
- INGESTION: INDUCE DO NOT INDUCE VOMITING. CONTACT PHYSICIAN IMMEDIATELY.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in Case Material is Released or Spilled:

- WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method:

- DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES.
- DO NOT PUNCTURE OR INCINERATE CONTAINER.
- DO NOT REUSE CONTAINER.
- WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be taken in handling and storing:

- DO NOT USE OR STORE NEAR HEAT OR OPEN FLAMES.
- EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: None

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREA.

Ventilation: Local Exhaust: ADEQUATE

Mechanical: N/A

Special: N/A

Other: N/A

Protective Gloves: N/A

Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHAMICALS ARE USED.

Other Protective Clothing or Equipment: N/A

Work/Hygienic Practices: WASH HANDS THOROUGHLY AFTER USE.