

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 584
IDENTITY: KWIK KOOL

Revision Date: 01/21/2007

Section I

Manufacturer's Name: QUEST CHEMICAL CORPORATION Telephone Numbers:
Address: 12255 FM 529 Emergency:
NORTHWOODS INDUSTRIAL PARK 800/255-3924
HOUSTON Information:
State: TX Zip Code: 77041 713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
CARBON DIOXIDE	124-38-9	5000 PPM	5000 PPM	N/A	___
MINERAL SEAL OIL	64741-44-2	5 MG/M3	5 MG/M3	N/A	___
PETROLEUM DISTILLATES	64742-54-7	5 MG/M3	10 MG/M3	N/A	___
_____	_____	_____	_____	_____	___
_____	_____	_____	_____	_____	___
_____	_____	_____	_____	_____	___
_____	_____	_____	_____	_____	___
_____	_____	_____	_____	_____	___
_____	_____	_____	_____	_____	___

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point: >500F Specific Gravity (water=1) 0.81
Vapor Pressure(mm Hg) N/A Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: <1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: CLEAR SPRAY, MILD OIL ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used): >265F TCC Flammable Limits: LEL:NE UEL: NE
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatibility (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY PRODUCE CARBON MONOXIDE.

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS. PROLONGED OVER-EXPOSURE MAY LEAD TO UNCONSCIOUSNESS AND DEATH. EYES: MAY CAUSE IRRITATION. SKIN: MAY CAUSE LOCALIZED DEFATTING. INGESTION: NAUSEA, VOMITING, DIARRHEA.
Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. INGESTION: IF IMMEDIATE ATTENTION IS GIVEN, INDUCE VOMITING. IN ALL CASES, IF SYMPTOMS PERSIST, CONSULT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN A WELL VENTILATED AREA
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment: N/A
Work/Hygienic Practices: WASH HANDS AFTER USE